






Ledline Listino Illuminazione stradale

ILLUMINAZIONE STRADALE LED CREE												
No.	Picture	Order Code	LED (pcs)	Size (mm) LxWxH	Voltage	Watt	Color (k)	Beam angle	Lumen (lm)	Base	LED Brand	Corrispondenza
1		S001	24	269×110×80mm	85-264VAC 12VDC 24VDC	30W	Warm white 2700-3500K Pure white 4000-5000K Cool white 5000-6500K	120/140(rectangular beam)	2500lm	E27/E40	CREE	70W HPS
2		S002	48	565×380×160mm	85-264VAC 12VDC 24VDC	48W	Warm white 2700-3500K Pure white 4000-5000K Cool white 5000-6500K	120/140(rectangular beam)	5136lm	Fissaggio su palo IP65	CREE	150W HPS
3		S003	96	680×380×160mm	85-264VAC 24VDC	96W	Warm white 2700-3500K Pure white 4000-5000K Cool white 5000-6500K	120/140(rectangular beam)	10272lm	Fissaggio su palo IP65	CREE	250W HPS
4		S004	144	830×380×160mm	85-264VAC	144W	Warm white 2700-3500K Pure white 4000-5000K Cool white 5000-6500K	120/140(rectangular beam)	15408lm	Fissaggio su palo IP65	CREE	350W HPS
5		S005	192	980×380×160mm	85-264VAC	192W	Warm white 2700-3500K Pure white 4000-5000K Cool white 5000-6500K	120/140(rectangular beam)	20544lm	Fissaggio su palo IP65	CREE	400W HPS

ILLUMINAZIONE A LED BRIDGELUX STRADALE

8		S007	20	953x398x1 32mm	100-240V AC 12-24VDC	21W	Warm white 2700-3500K Pure white 4000-5000K Cool white 5000-6500K	130°×80°	2800lm	Cavo IP66	Bridgelux	70W HPS
9		S008	40	1200x398x 132mm	100-240V AC	51W	Warm white 2700-3500K Pure white 4000-5000K Cool white 5000-6500K	130°×80°	5580lm	Cavo IP66	Bridgelux	150W HPS
10	 © CB CE	S009	40	953x398x1 32mm	100-240V AC	51W	Warm white 2700-3500K Pure white 4000-5000K Cool white 5000-6500K	130°×80°	5580lm	Cavo IP66	Bridgelux	150W HPS
11	 © CB CE	S010	80	777x398x1 32mm	100-240V AC	99W	Warm white 2700-3500K Pure white 4000-5000K Cool white 5000-6500K	130°×80°	7770lm	Cavo IP66	Bridgelux	200HPS
12		S011	180	953x398x1 32mm	100-240V AC	145W	Warm white 2700-3500K Pure white 4000-5000K Cool white 5000-6500K	130°×80°	16740lm	Cavo IP66	Bridgelux	400W HPS

ARREDO URBANO LED CREE

No.	Picture		LED (pcs)	Size (mm) LxWxH	Voltage	Watt	Color (k)	Beam angle	Lumen (lm)	Base	LED Brand	
13		SU001	\	Φ400mm/ Φ500mm	\	\				IP65	\	
14		SU00229	24	Φ560mmx 815mm	100-277V AC	29W	White 6500K Commercial White 4500k Warm White 3200K	360°	1529/1426 /1147lm	Palo IP65	CREE	
15		SU00268	54	Φ560mmx 815mm	100-277V AC	68W	White 6500K Commercial White 4500k Warm White 3200K	360°	3316/3102 /2568lm	Palo IP65	CREE	
16		SU00284	72	Φ560mmx 815mm	100-277V AC	84W	White 6500K Commercial White 4500k Warm White 3200K	360°	4155/3870 /3206lm	Palo IP65	CREE	
17		SU00329	24	Φ560mmx 1317mm	100-277V AC	29W	White 6500K Commercial White 4500k Warm White 3200K	360°	2104/1988 /1642lm	Palo IP65	CREE	
18		SU00368	54	Φ560mmx 1317mm	100-277V AC	68W	White 6500K Commercial White 4500k Warm White 3200K	360°	4567/4234 /3548lm	Palo IP65	CREE	
19		SU00384	72	Φ560mmx 1317mm	100-277V AC	84W	White 6500K Commercial White 4500k Warm White 3200K	360°	5705/5244 /4310lm	Palo IP65	CREE	